PAB Materials Test System	
Date of Receipt	8/13/2009
Sample Name/Description	LED/ High Efficiency Green
	MV54643(HLMP-1503)
Sample	
Composition:	GaPh light emitting diode encapsulated in epoxy with metal leads
Picture Location:	elog 7/31/09
Density:	x
Weight:	25.9g (201 LEDs), 215g (LEDs+metal box)
Dimensions/Area:	200 LEDs, single LED:green package 3.1x4.5mm, 2 leads 0.5x26.4mm
Source:	Walter Jaskierny
Preparation:	Carefully cleaned with ethanol saturated wipes and put into
	cleaned metal box
Submerging in LAr or LN2	х
Zero Test	х
Time in the airlock(hrs)	96h total (57h no purging, because gas run out over the weekend)
Purge:	start 7/31/09, 38h with gas from the bottle , and 1h with Luke gas
Vacuum:	x
Vapor Test 1	
Start Time/Date, End Time/Date:	8/4/09 10:00am, 8/5/9 9:20am
PrM run # :	5678
Condenser state:	on
Filter state:	on
O2 reading:	0.35ppb
H2O reading:	3.5 ppb
Temperature:	225K
Lifetime:	9ms- before moving to vapor, 6ms - 3min after
Vapor Test 2	
Start Time/Date, End Time/Date:	8/5/09 9:20am, 8/6/09 12:00pm
PrM run # :	5691
Condenser state:	on
Filter state:	on
O2 reading:	0 ppb (-0.045)
H20 reading:	3.4 ppb
Temperature:	120K - 135K
Liquid Test	3.3ms - 5min after moving to lower temp., 5.3ms - 26 hours after
-	X
Start Time/Date, End Time/Date: PrM run #:	
Condenser state:	
Filter state/settings: O2 reading:	
H20 reading:	
Temperature: Lifetime:	
Liquid level :	
Results & Comments	LEDs were submerged in LAr for 1-2min between Vapor Test 1 and
	Vapor Test 2 because we moved it too low in Luke.
	LEDs(HLMP-1503) can be used in low temperatures.
	LED historical data plot is in eLog 8/6/09



